



# SEAT COVERS - FRONT SET

Suitable to assist in fitting all front seat covers from UK Custom Covers

## SINGLE SEAT COVER (DRIVER OR PASSENGER)

- 1 Remove any headrests from your seats if applicable.

Note: Some vehicles have headrests which differ between seats.  
We would recommend noting which headrest attaches to which seat.

- 2 If your seat back covers are separate from the base covers:

- a. Slide the back covers down over the seat backs, ensuring any airbag slits or tags are correctly positioned.



If your seat back covers are attached in one piece with the base covers:

- a. Slide the back covers down over the seat back, ensuring any airbag slits or tags are correctly positioned, and any velcro for armrests is undone.
- b. Tilt the back of the seat forwards, pushing the foam tube on the inside of the cover (pictured) fully through the crease between the seat back and base.
- c. Tilt the seat back, locking the foam tube in place securely and refasten any armrest velcro.

- 3 Slide the base covers over the seat base, ensuring all corners are snug.

- 4 Some of our seat covers might have additional fittings. Using the images in the **additional fitment types** page, secure any additional fittings.

- 5 Slide the armrest cover over the armrest if supplied, ensuring any elasticated or velcro fittings are on the inside.

- 6 Slide the headrest cover over the headrest, tightening and securing where necessary.

Note: Some vehicles have headrests which differ between seats. If your headrest cover doesn't fit on the first try, test on the other headrests to find the correct match.

- 7 Re-attach headrests to your seats, and push any extra material under your headrest adjustment fixtures.




# SEAT COVERS - FRONT SET

Suitable to assist in fitting all front seat covers from UK Custom Covers

## DOUBLE SEAT COVER (PASSENGER)

- 1 Remove any headrests from your seats if applicable.
- 2 Fully unzip or unfasten the velcro on the back covers and pull over the seats to the base, ensuring the seatbelt isn't underneath.
- 3 Zip up or refasten the velcro to secure the covers.
- 4  If applicable, attach the release buckle around the seat frame - position on your covers may vary, lifting seat bases may be necessary.
- 5 If the seats have a split base, line up the seat base covers with your seats, ensuring that the shapes match your seats.  
Note: Most vehicles have different left and right seat bases - match the shape of each before fitting.
- 6 Starting at the back, slide the base covers over the seats. If possible, lifting up the seats can make this easier. Ensure all corners are snug. Some covers might have additional fittings. Using the images in the **additional fitment types** page, secure any additional fittings.
- 7 Slide the headrest covers over the headrests, tightening and securing where necessary.  
Note: Some vehicles have headrests which differ between seats. If your headrest cover doesn't fit on the first try, test on the other headrests to find the correct match.
- 8 Re-attach headrests to your seats, and push any extra material under your headrest adjustment fixtures.





## SEAT COVERS - FRONT SET

Suitable to assist in fitting all front seat covers from UK Custom Covers

### ADDITIONAL FITMENT TYPES



#### **Velcro cinch strap under the seat base:**

Loop the velcro strap through the buckle and tighten as necessary.



#### **Elastic & metal hooks:**

If necessary, attach hooks to elastic strap by looping or tying.  
Attach hook to the seat frame, ensuring a secure fit.  
Hook design might differ.



#### **Side release buckle:**

Any side release buckles can be pulled tight and attached securely.



#### **Foam bar flap:**

Push any foam bars between seat creases or plastic mouldings, ensuring a secure fit.

